

BiPAC 7402VGO

VoIP/802.11g ADSL2+ VPN Firewall Router

- Two FXS ports for connecting to regular telephones
- One RJ-11 FXO port for PSTN Lifeline support
- Secured Virtual Private Network (VPN) with powerful 3DES
- 802.11g Wireless AP with WPA Support
- High speed Internet Access with ADSL, ADSL2/2+ firmware upgradable
- IGMP Snooping for video service
- SOHO Firewall Security with DoS Prevention and SPI
- QoS Control for Traffic Prioritization and Bandwidth Management
- Parental Control with URL Content Filtering and Packet Filtering
- Universal Plug and Play (UPnP) compliance
- Dynamic Domain Name System (DDNS)
- Ease of Use with Quick Installation Wizard and Auto-scan ADSL Settings
- Ideal for SOHO and Office Users

**▲ BiPAC 7402VGO**

Benefits

Economical Phone Calls

Connecting the router to existing telephone line, the router enables making cost-saving, toll-quality calls via ADSL Internet connection. It complies with the most popular industrial standard, SIP protocol, to ensure the interoperability with SIP devices and major VoIP Gateways. The router supports call waiting, silence suppression, voice activity detection (VAD), comfort noise generation (CNG), line echo cancellation, caller ID (Bell 202,V23) and so on.

Virtual Private Network

The router supports embedded Virtual Private Network (VPN) protocols and up to 16 simultaneous IPsec VPN tunnels for establishing private encrypted tunnels over the public Internet to ensure transmission security between two or more sites. With built-in DES/3DES accelerator, the router enhances the IPsec VPN performance significantly.

Express Internet Access - ADSL2/2+ firmware upgradable

The router complies with ADSL worldwide standards. It supports downstream rate up to 8Mbps with ADSL, capable up to 12/24 Mbps with ADSL2/2+, and upstream rate up to 1 Mbps. Users enjoy not only high-speed ADSL services but also broadband multimedia applications such as interactive gaming, video streaming and real-time audio much easier and faster than ever.

Mobility and Protection

With integrated 802.11g Wireless Access Point in the router, the device offers a quick and easy access among wired network, wireless network and broadband connection (ADSL) with single device simplicity, and as a result, mobility to the users. In addition to 54 Mbps 802.11g data rate, it also interoperates backward with existing 802.11b equipment. The Wireless Protected Access (WPA) supported features enhance the security level of data protection and access control via Wireless LAN.

Smooth and Responsive Net Connection

Quality of Service (QoS) gives you full control over which type of outgoing data traffic should be given priority by the router, ensuring important data like gaming packets, customer information, or management information move through the router at lightning speed, even under heavy load. The QoS features are configurable by source IP address, destination IP address, protocol, and port. You can throttle the speed at different type of outgoing data pass through the router, to ensure users don't saturate upload bandwidth, or office browsing doesn't bring client web serving to a halt.

Extra Back Up - Lifeline Support

Billion's BiPAC 7402VGP integrates another RJ-11 FXO port for inbound and outbound calls transmitted through PSTN. Users can receive phone calls from PSTN while enjoying VoIP call service at the same time. In addition, the device automatically fallbacks to lifeline POTS to enable making normal phone calls when there is power outage, or when the Internet connection is down.



Feature & Specification

ADSL Compliance

- Compliant with ADSL Standard
 - Full-rate ANSI T1.413 Issue 2
 - G.dmt (ITU G.992.1)
 - G.hs (ITU G.994.1)
 - ADSL over ISDN/U-R2
- Capable of ADSL2 Standard
 - G.dmt.bis (ITU G.992.3)
- Capable of ADSL2+ Standard
 - G.dmt.bisplus (ITU G.992.5)

Network Protocols and Features

- NAT, static routing and RIP-1/2
- Universal Plug and Play (UPnP) Compliant
- Dynamic Domain Name System (DDNS)
- Virtual Server and DMZ
- SNTP, DNS relay and IGMP proxy
- POP3 (email account checking)
- IGMP Snooping for video service

Firewall

- Built-in NAT firewall
- Stateful Packet Inspection (SPI)
- Prevent DoS attacks including IP Spoofing, Land Attack, Smurf
 - Attack, Ping of Death, TCP SYN Flooding, etc.
- Packet Filtering - port, source IP address, destination IP address,
 - MAC address
- URL Content Filtering - string or domain name detection in URL
 - string

VoIP

- Two RJ-11 FXS ports for connecting to regular telephones
- One RJ-11 FXO port for receiving/making calls from/to PSTN for lifeline support
- Compliant with SIP standard (RFC3261)
- Supports G.711 A/μ law, and G.729A Audio Codec standards
- Supports Telephony Features: call waiting, silence suppression, voice
 - activity detection (VAD), comfort noise generation (CNG), G.168 line
 - echo cancellation, caller ID (Bell 202,V23)
- Make a PSTN call by pre-fix number
- Voice over data, QoS control to ensure higher voice quality
- Adaptive jitter buffer support
- Automatic fallback to lifeline POTS when the router power down or VoIP service is not available.

Wireless 802.11g

- Compliant with IEEE 802.11g and 802.11b standards
- 2.4 GHz - 2.484G Hz frequency range
- Up to 54 Mbps wireless operation rate
- 64/128 bits WEP supported for encryption
- WPA support



▲ Application Diagram (BiPAC 7402VGO)

Quality of Service Control

- Support DiffServ approach
- Traffic prioritization and bandwidth management based-on IP
 - protocol, port number and address

ATM and PPP Protocols

- ATM Adaptation Layer Type 5 (AAL5)
- Multiple Protocol over AAL5 (RFC 2684, formerly RFC 1483)
- Bridged or routed Ethernet encapsulation
- VC and LLC based multiplexing
- PPP over Ethernet (PPPoE)
- PPP over ATM (RFC 2364)
- Classical IP over ATM (RFC 1577)
- MAC Encapsulated Routing (RFC 1483 MER)
- OAM F4/F5

Virtual Private Network (VPN)

- 16 IPSec VPN Tunnels
 - 8 L2TP VPN Tunnels (Dial-in: 4, Dial-out: 4)
 - 8 PPTP VPN Tunnels (Dial-in: 4, Dial-out: 4)
- Embedded IPSec & PPTP client/server
- IKE key management
- DES, 3DES and AES encryption for IPSec
- Embedded powerful 3DES
- MPPE Encryption for PPTP
- L2TP within IPSec
- L2TP/PPTP/IPSec pass-through

Management

- Quick Installation Wizard and Auto-scan ADSL settings
- Web-based GUI for remote and local management
- Firmware upgraded and configuration data upload and download via
 - Web-based GUI
- Firmware upgradeable to ADSL2/ADSL2+ standards
- Embedded Telnet server for remote and local management
- Available Syslog monitoring
- SNMP v3, MIB-I and MIB-II support
- Support DHCP server/client/relay

Hardware Specification

Physical Interface

- WLAN: detachable antenna
- WAN: ADSL port
- Telephone: 2-port FXS
 - 1-port FXO
- LAN: 3-port 10/100M auto-crossover (MDI/MDI-X) Switch
- Console: PS2
- Factory default reset button
- Power jack
- Power switch

Physical Specification

- Dimensions: 8.27" x 5.83" x 1.42"
(210mm x 148mm x 36mm)

Power Requirement

- Input: 12V DC, 1.2A

Operating Environment

- Operating temperature: 0 ~ 40°C
- Storage temperature: -20 ~ 70°C
- Humidity: 20 ~ 95% non-condensing

All the specifications are subject to changes without prior notice.

Billion Electric Co., Ltd.

8F, No.192, Sec.2, Chung Hsing Road,
Hsin Tien City, Taipei Hsien, Taiwan

TEL : +886-2-2914-5665

FAX : +866-2-2918-6731, +886-2-2918-2895

E-mail : sales@billion.com